

With a printing capacity of up to 750 pages per hour, the PP 407 is one of the fastest 24-pin printers on the market



PP 407 with the options printer stand and paper stacker

The PP 407 is applied where quick and cost-effective printing on fanfold paper is required. This printer model is perfectly designed for continuous batch printing of lists, barcodes and graphics on labels or multi-part formsets. Retail companies, financial institutes, logistics and industrial environments use the PP 407 in professional applications. The modular connection concept of the PP 407 allows the integration into all major host systems and network. The extreme long-life XXL ribbon cassettes in combination with the well proved matrix technology provide a very low Total-Cost-of-Ownership (TCO).

- Heavy duty 24-wire dot matrix printer
- Performance:
 - 700 characters per second
 - up to 510 lines per minute
 - up to 762 pages per hour
 - 40,000 pages per month
- Plug & Print: Plug-in tractor cassettes for easy paper loading
- Two fanfold papers alternatively accessible
- Flatbed technology for reliable and straight paper transport
- Automatic Gap Control (AGC)
- 1 + 5 excellent copies
- 14 fonts including block characters 13 barcodes
- high-precision uni- and bidirectional printing
- Long life ribbon up to 30 million characters
- Connectivity to all major host systems and networks
- Optional Silent-Kit for additional noise reduction of ~75%



TECHNICAL DATA

Printer Specification

Technology:	serial impact dot matrix
Printhead:	24 wires, 0.25 mm (0.01 inch) needle diameter; life time 400 million characters
Print mode:	Data (DQ), Near Letter (NLQ) and Letter Quality (LQ)
Print format:	136 characters at 10 cpi
Ribbon:	XXL nylon ribbon cassette, black (up to 30 million characters)
Dimensions:	740 x 370 x 325 mm (WxDxH) (29.6 x 14.8 x 13 inches)
Weight:	~ 28.5 kg (62 lb)
Diagnostics:	selftest, hexdump, remote diagnostics via interface
Operator Panel:	16 digit LCD display, trilingual (German, English, French)
Rated voltage:	200-240 V, 50-60 Hz (optionally 100-125 V, 50-60 Hz)
Power input:	120 W, 20 W standby
Environmental temperature:	operating: +10 to +35 °C (+50 to +95°F) 20 to 80% rel. humidity storage: -40 to +70 °C (-40 to +158°F) 5 to 85% rel. humidity
Noise level:	55 dB(A) acc. to ISO 7779
Agency approvals:	CE

Performance

Print speed: (at 10 cpi)	mode	cps	mode	lpm
	DQ:	700	DQ: 40 characters per line	510
	NLQ:	350	DQ: 60 characters per line	430
	LQ:	175	DQ: 80 characters per line	370
Throughput: (ECMA 132, letter, 1-ply)	mode	fanfold (at 10 cpi)		
	HSD:	762 pages per hour		
	DQ:	750 pages per hour		
	NLQ:	520 pages per hour		
	LQ:	320 pages per hour		
Duty cycle:	typical 40,000 pages per month			
MTBF:	10,000 hours at 30% duty cycle			

Paper Handling

Paper paths:	flatbed technology, 2 inputs for fanfold paper, 1 output for fanfold paper, paper path selectable via software or operator panel
Paper input:	two independent, easy to plug-in tractor cassettes for fanfold paper; push tractor with park position to the rear with zero tear-off
Paper output:	
Paper weight:	formsets up to 350 g/ m ² (14 oz/ m ²), 60 to 90 g/m ² (2.4 to 3.6 oz/ m ²) per sheet; single-layer up to 240 g/m ²
Paper width:	4 to 16 inch (100 to 400 mm)
Form feed speed:	20 inch/second; 25 ms per line feed
Automatic GAP Control (AGC):	optimizes automatically the distance between print head and paper according to paper thickness
Paper run control:	allows unattended printer operation
Copies:	1 original + 5 copies, maximum paper thickness 0.5 mm (0.02 inch)

Connectivity

PERSONALITY MODULE SER/PAR/USB

Interfaces:	parallel IEEE 1284, serial RS-232 (DSUB 9), USB 2.0
Emulations:	IBM Printer XL24 (AGM), Epson LQ 2550/1060, ESC/P2
Buffer:	selectable up to 176 KByte
Character sets:	ISO 8859/1, ISO 8859/9, 8859/15; IBM Set 1/Set 2 into 14 national versions; IBM Code Pages 437, 850, 852, 857, 858, 860, 863, 865; Epson Ext. Char. Set in 15 national versions; Eastern European character sets 771, 773, 774, 775, 1125, 1251; Baltic RiM, Greek, CZ, HUN, Russia, Win Lat 2
Fonts:	Draft quality: Data and Data Large; Near letter and letter quality: Courier, OCR-A, OCR-B, Orator, Prestige, Roman, Script, Sans serif bold, italic, shadow, outline, double strike, underline, double underline, overline, strike through, sub/superscript, double to octuple, for Data Large 99-fold size
Pitches:	10, 12, 15, 17.1, 18 and 20 cpi, proportional
Line spacing:	2, 3, 4, 6, 8, ... 360 lpi
Barcode:	EAN 8, EAN 13, UPC-A, UPC-E, Postnet, KIX Code, Code 39, Code 93, Code 128 (incl. EAN 128), Codabar, 2 of 5 industrial, 2 of 5 interleaved, and MSI Mod 10/10 (horizontal or vertical)
Graphics:	360 x 360 dpi max. (uni-/ bidirectional)
Macros:	parameter settings for up to four individual printer configurations, selectable via software or operator panel

PERSONALITY MODULES

Emulations Interface	
IBM/Epson:	Serial/Parallel/USB or Serial/Ethernet/USB
IPDS:	Ethernet
IBM-IGP 10/20/40:	Parallel or Ethernet
HP 2934/2235:	Serial/Parallel/USB or Serial/Ethernet/USB
Genicom:	Serial/Parallel/USB or Serial/Ethernet/USB
Stringchange:	Parallel or Ethernet

Printer drivers for Windows and SAP R/3 device types are available for download at <http://www.psi-matrix.eu>

Options

Tractor Cassette:	Additional tractor cassettes for quick exchange of loaded media.
Printer Stand:	Dimensions: 635 x 660 x 840 mm (WxDxH), weight: approx. 25 kg (55 lb)
Stacker Option:	System to be integrated into the stand for orderly stacking of fanfold paper, capacity: ~ 2.000 pages
Sound Cover:	For an optimal sound insulation in application with the Printer Stand, dimensions: 910 x 575 x 420 mm (WxDxH), weight: approx. 33 kg
Sound Cabinet:	Replacement of Printer Stand and Sound Cover, dimensions: 900 x 715 x 1.150 mm (WxDxH), weight: approx. 80 kg
Schalldämmkit:	Zur Reduzierung des Geräuschpegels um 75%

(*) LPM = Lines per Minute

This is only an extract of the product specification. For a detailed specification it is referred to the comprehensive product documentation. Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.

Psi Matrix GmbH

Hommesswiese 116a
57258 Freudenberg, Germany
Tel: 02734 284 77 500
Fax: 02734 284 77 599

e-mail: sales@psi-matrix.eu
Internet: www.psi-matrix.eu

professional printing solutions

