

PR 9

The Flexible Multiforms Printer for Banking, Public Administration and Industry



- 24-wire flatbed dot matrix printer
- Compact and modern design
- Up to 570 cps (10 cpi)
- User-friendly man-machine interface
- Low cost of ownership
- Long-living print head
- Automatic Gap Control (AGC) for premium print quality
- Automatic document edge sensing and alignment
- Serial (RS-232), Parallel and USB 2.0 Interfaces
- Fully compatible with new international standards in financial applications

The PR 9 is the economic solution for fast and reliable document printing.

The PR 9 is a flexible transactional printer for banking, public administration, and industrial applications. Latest innovative technologies like e.g. automatic document edge sensing and alignment allow fast and reliable printing of various documents like pass books, tickets, prescriptions, and carbon paper with up to 7 copies. Optionally, continuous paper can also be processed.

A durable print head and long-life consumables as well as the user-friendly operation keep the total cost of ownership extremely low.



PR 9

TECHNICAL DATA

Printer Specification

Technology:	Serial impact dot matrix
Printhead:	24 wires 0.25 mm (0.01 inch) needle diameter, Life time > 500 million dots/needle
Print mode:	High speed draft (HSD), draft quality (DQ), near letter quality (NLQ) and letter quality (LQ)
Print format:	94 characters at 10 characters per inch (cpi)
Resolution:	360 x 360 (HxV)
Ribbon:	Cartridge nylon ribbon black, 5 million characters
Dimensions:	398 x 296 x 201 mm (WxDxH)
Weight:	9 kg
Diagnostics:	Selftest, hexdump, remote diagnostics via interface, Unique ID-number
Operation Panel:	LCD with 2 lines, each with 20 characters, 5 push buttons, 4 status LED's
Rated Voltage:	240 VAC ± 10%, 50 - 60 Hz
Power Consumption:	Operating approx. 170 W, 5.5W in sleep mode
Environmental:	Operating: + 5 to +35°C 35 to 85% rel. humidity Storage: -10 to +60 °C 10 to 90% rel. humidity
Noise level:	54 dB(A) according ISO 7779
Agency Approvals:	CE, CCC

Paper Handling

Paper path:	Flatbed technology
Paper Input:	Cut sheets and passbooks from front, with: automatic alignment of all kinds of documents and automatic document edge sensing
Paper output:	To the rear or front depending on settings
Paper weight:	30 to 160 g/m ² , Formsets up to 240 g/m ²
Passbook width:	110 mm - 241 mm, maximum thickness 2 mm
Paper width:	80 mm - 245 mm
Form feed:	> 32 cm/second
Automatic Print	Printing force can be optimized automatically depend- ing on paper thickness
Force Control (PFA):	
Copies:	1 original + 6 copies

Performance

Print speed:	HSD: 570 cps (10 cpi)	DQ: 414 cps NLQ: 207 cps LQ: 140 cps
Reliability:	MTBF: 10.000 hours	

Connectivity

Interface:	Parallel Centronics / Serial RS-232 / USB 2.0
Emulations:	IBM Proprinter II/XL24 (AGM), Olivetti PR2E/PR40+, OKI 5530SC, Epson LQ1600K, IBM 4722, IBM 9068
Buffer:	512 KByte
Character Sets:	ISO 8859/1-9, SO 8859/15, Olivetti code tables (7bit & 8bit), Code Pages 210, 220, 437, 850-858, 860-866, 1250-1257, Epson Ext.Char.Set in 13 national versions
Fonts:	Roman, Sans Serif, Italic, OCR-A, OCR-B, Chinese and other national character sets
Character attributes:	Bold, underline, overline, sub-/superscript, double width, double height, double width and height, horizontal and vertical expansion, italic
Pitches:	5, 10, 12, 12.9, 15, 16.6, 17.1, 18, and 20 cpi, proportional and compression
Barcodes:	EAN8, EAN12, UPC-A, UPC-E, Code 39, Code 128, Codabar, 2 of 5, Industrial, 2 of 5 Interleaved
Graphics:	9 pin mode density: 60, 72, 80, 120, 240 dpi 24 pin mode density: 60, 120, 180, 240, 360 dpi

Printer drivers for Windows are available for download at

Options

Interfaces:	Parallel Serial RS-232 USB 2.0
--------------------	--------------------------------------

This is only an extract of the product specification. For a detailed specification it is referred to the comprehensive product documentation. Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.

PSi Matrix GmbH

Hommesswiese 116a

57258 Freudenberg, Germany

Tel: 02734 284 77 550 e-mail: sales@psi-matrix.eu

Fax: 02734 284 77 599 Internet: www.psi-matrix.eu